



HATSAN ARMS COMPANY



AT44 PA

10-SHOT PUMP ACTION PCP AIR RIFLE

www.hatsan.com.tr



AT44PA

10-Shot Pump Action PCP Air Rifle



- 10-shot, manual loading, pump action, pre-charged pneumatic (PCP) air rifle.
- Precision rifled choked barrel for accuracy, threaded for 1/2" UNF sound moderator & fitted muzzle cap.
- Available in .177 (4.5 mm) and .22 (5.5 mm) calibers.
- Thumbhole synthetic ambidextrous stock with raised montecarlo checkpiece.
- Elevation & fit angle adjustable rubber butt pad.
- Detachable 10-shot rotary magazine. Comes with extra magazine in the box.
- Detachable air cylinder tube (180 cc) enabling to use spare air cylinders.
- Built-in pressure gauge on the air cylinder to monitor the cylinder pressure.
- Standard quick-fill nozzle & air cylinder discharging cap supplied in the box.
- Dovetail groove receiver for both 11 mm and 22 mm scope mounts.
- Overall blued finish, black anodized receiver.
- Resettable Manual Safety
- "Anti-double pellet feed" mechanism preventing more than one pellet loading into barrel.
- Adjustable rear & front sight with Truglo fiber optics.
- 2-stage adjustable match trigger for trigger travel and trigger pull force.
- Gold plated metal trigger & metal trigger guard.



Elevation & fit angle adjustable rubber butt pad.



- Resettable Manual Safety.
- Scope mount rail good for both 11 mm and 22 mm scope mounts.
- 10-shot magazine.
- Micro adjustable rear sight.
- Gold plated 2-stage adjustable match trigger for trigger travel and trigger pull force.



Left side view

SPECIFICATIONS

Model	Caliber	Max. Muzzle Velocity (*)	Shots Per Magazine	Fill Pressure	Shots Per Fill	Stock	Overall Length	Barrel Length	Weight	Fiber Optic Sights Diameters	
										Rear Sight	Front Sight
AT44PA	4.5 mm / .177 cal	325 m/s (1070 fps)	10	200 BAR	90	Advanced Polymer with ThumbHole & raised montecarlo checkpiece	1000 mm (39.4")	495 mm (19.4")	3.8 kg (8.4 lbs)	0.9 mm (.035") green	1.5 mm (.060") red
	5.5 mm / .22 cal	295 m/s (970 fps)	10	200 BAR	80						

* Above velocity figures may show differences depending on the pellet weight and geometry.

* Lower muzzle velocities can be arranged according to the muzzle energy restriction of any country. Above maximum muzzle velocity figures are when there is no muzzle velocity/energy restriction is implemented on the rifle and when measured at peak value as the velocity will decrease as the pressure in the air cylinder decreases.



TRUGLO
Adjustable front sight

1/2" UNF threaded muzzle and fitted muzzle cap.

Detachable 180 cc air cylinder for 200 bar fill pressure with built in pressure gauge.